



美国Control (DeviceMaster) - 工业级串口联网服务器



DeviceMaster RTS	RTS VDC 1-Port DB9 (99440-4)	RTS 2-Port 1E (99480-0)	RTS 2-Port 2E (99481-7)	RTS DB9 2-Port 1E (99550-0)	RTS DB9 2-Port 2E (99560-9)
DeviceMaster UP Modbus	UP VDC 1-Port DB9 Modbus (99501-2)	UP 2-Port 1E Modbus (99532-6)	UP 2-Port 2E Modbus (99542-5)	UP DB9 2-Port 1E Modbus (99552-4)	UP DB9 2-Port 2E Modbus (99562-3)
硬件					
10/100Base-TX以太网口数	1	1	2	1	2
RS232/422/485串口数	1 x RS232/422/485	2 x RS232/422/485	2 x RS232/422/485	2 x RS232/422/485	2 x RS232/422/485
串口Baud Rate	300 to 230.4Kbps	300 to 230.4Kbps	300 to 230.4Kbps	300 to 230.4Kbps	300 to 230.4Kbps
串口界面	DB9M	Screw Terminal	Screw Terminal	DB9M	DB9M
电源输入	5-30VDC Terminal (2.5W)	5-30VDC Terminal (1.5W)	5-30VDC Terminal (2W)	2 x 6-30VDC Terminal (1.6W)	2 x 6-30VDC Terminal (2W)
串口突波保护	15KV	25KV	25KV	25KV	25KV
环境					
MTBF	46.2 Years	58.57 Years	45.66 Years	58.57 Years	49.5 Years
外壳	不锈钢	UL94-V0 塑料	UL94-V0 塑料	UL94-V0 塑料	UL94-V0 塑料
尺寸	73.1(W) x 22.6(H) x 92.7(D)	22.6(W) x 99(H) x 111(D)	45.2(W) x 99(H) x 111(D)	22.9(W) x 99(H) x 114.8(D)	45.7(W) x 99(H) x 114.8(D)
操作温度	-37~74°C	-37~74°C	-37~74°C	-37~74°C	-37~74°C
安装	导轨/平板	导轨	导轨	导轨	导轨
驱动					
Windows 2000/Server 2008/XP	●	●	●	●	●
Windows Vista	●	●	●	●	●
Windows 7	●	●	●	●	●
Linux	●	●	●	●	●
软件					
TCP, UDP Socket	●	●	●	●	●
PortVision® Plus远程管理	●	●	●	●	●
Web-based设置界面	●	●	●	●	●
SSL & SSH加密	(99440-4)	(99480-0)	(99481-7)	(99550-0)	(99560-9)
E-mail事件告警	(99440-4)	(99480-0)	(99481-7)	(99550-0)	(99560-9)
DualConnectPlus™	(99501-2)	(99532-6)	(99542-5)	(99552-4)	(99562-3)
Industrial Ethernet Protocol					
Modbus/TCP	(99501-2)	(99532-6)	(99542-5)	(99552-4)	(99562-3)
通过认证					
RoHS 2002/95/EC	●	●	●	●	●
CE/FCC/UL/RoHS	●	●	●	●	●
NEMA TS2	●	●	●	●	●
Warranty	5 Years	5 Years	5 Years	5 Years	5 Years

美国Control (DeviceMaster) - 工业级串口联网服务器



DeviceMaster RTS	RTS 4-Port DB9 (99445-9)	RTS 8-Port DB9 (99448-0)	RTS 16-Port RJ45 (99455-8)	RTS 32-Port RJ45 (99456-5)
DeviceMaster UP Modbus	UP 4-Port DB9 Modbus (99521-0)			
硬件				
10/100Base-TX以太网口数	2	2	1	1
RS232/422/485串口数	4 x RS232/422/485	8 x RS232/422/485	16 x RS232/422/485	32 x RS232/422/485
串口Baud Rate	300 to 230.4Kbps	300 to 230.4Kbps	300 to 230.4Kbps	300 to 230.4Kbps
串口界面	DB9M	DB9M	RJ45	RJ45
电源输入	9-30VDC Terminal External Power Supply included: 90-260VAC(US/EU) input	9-30VDC Terminal External Power Supply included: 90-260VAC(US/EU) input	90-260VAC (US/EU Cord)	90-260VAC (US/EU Cord)
串口突波保护	15KV	15KV	15KV	15KV
环境				
MTBF	25.0 Years	21.5 Years	8.1 Years	6 Years
外壳	钢制	钢制	钢制	钢制
尺寸	272.3(W) x 36.1(H) x 160.0(D)	272.3(W) x 45.0(H) x 160.0(D)	438.1(W) x 43.7(H) x 274.3(D)	438.1(W) x 43.7(H) x 274.3(D)
操作温度	-37~74°C	-37~74°C	-37~74°C	-37~74°C
安装	平板	平板	1U 机架	1U 机架
驱动				
Windows 2000/Server 2008/XP	●	●	●	●
Windows Vista	●	●	●	●
Windows 7	●	●	●	●
Linux	●	●	●	●
软件				
TCP, UDP Socket	●	●	●	●
PortVision® Plus远程管理	●	●	●	●
Web-based设置界面	●	●	●	●
SSL & SSH加密	(99445-9)	●	●	●
E-mail事件告警	(99445-9)	●	●	●
DualConnectPlus™	(99521-0)			
Industrial Ethernet Protocol				
Modbus/TCP	(99521-0)			
通过认证				
RoHS 2002/95/EC	●	●	●	●
CE/FCC/UL/RoHS	●	●	●	●
NEMA TS2	●	●		
Warranty	5 Years	5 Years	5 Years	5 Years