

Korenix Industrial Product Selection Guide - Serial Device Server



JetPort 5216



JetPort 5208



JetPort 5604



JetPort 5604i

	Rackmount Serial Server	Rackmount Serial Server	Redundant Serial Server	Isolation Redundant Serial Server
Interface				
Number of Ports:10/100Base-TX	1	1	2(Redundant)	2(Redundant)
Number of Serial Ports	16*RS232	8*RS232	4*RS232/422/485	4*RS422/485 with 2KV Isolation
AC Power Input	100~240 VAC	100~240 VAC		
Power Terminal			DC12~48V	DC12~48V
Power Jack			DC12~48V	DC12~48V
Fault Relay Output			4 Digital Inputs 2 Digital Outputs	4 Digital Inputs 2 Digital Outputs
1200VAC HIPOT			•	•
Mechanical				
Aluminum Case			•	•
Dimensions (unit=mm)	437.2(W) x 214(H) x 44(D), 1U Rackmount		145(W) x 46.5(H) x 120(D)	145(W) x 46.5(H) x 120(D)
Case Protection			IP 31	IP 31
Operating Temperature	0~50°C	0~50°C	-10~70°C	-10~70°C
DIN-Rail Kit			•	•
Protocols				
Web-based Configuration	•	•	•	•
Windows Utility	•	•	•	•
Secured HTTPS,SSH	•	•	•	•
RTTD, Redundant Dual Ethernet			•	•
SNMP V1/V2C	•	•	•	•
SMTP(e-mail warning)			•	•
Syslog	•	•	•	•
Certifications				
Regulatory Approvals:CE / FCC / UL	•	•	CE / FCC	CE / FCC
RoHS / WEEE	•	•	•	•

Korenix Industrial Product Selection Guide - Serial Device Server



	Redundant Serial Server	Fiber Serial Server	Wireless Device Server	Serial Server
Interface				
Number of Ports:10/100Base-TX	2(Redundant)		1	1
Number of Ports: WLAN			1	
Number of Ports:100Base-FX (Multi Mode Fiber)		JetPort 5601f-m		
(Single Mode Fiber)		JetPort 5601f-s		
Number of Serial Ports	1* RS232/422/485	1* RS232/422/485	1* RS232/422/485	1* RS232
Power Terminal	DC12~48V	DC12~48V	DC12~48V	
Power Jack	DC9~30V	DC9~30V	DC12~48V	DC9~30V
Fault Relay Output				
1200VAC HIPOT	•	•	•	•
Mechanical				
Aluminum Case	•	•	•	•
Dimensions (unit:mm)	96.1(W) x 29.6(H) x 99(D)		96.1(W) x 29.6(H) x 124(D)	78.5(W)x29.2(H) x 79.6(D)
Case Protection	IP 30	IP 30	IP 30	IP 30
Operating Temperature	-10~70°C	-10~70°C	-10~55°C	0~60°C
DIN-Rail Kit	•	•	•	•
Protocols				
Web-based Configuration	•	•	•	•
Windows Utility	•	•	•	•
Secured HTTPS,SSH	•	•	•	
RTTD, Redundant Dual Ethernet	•			
SNMP V1/V2C	•	•	•	•
SMTP(e-mail warning)	•	•	•	•
Syslog	•	•	•	•
Certifications				
Regulatory Approvals:CE / FCC / UL	•	•	CE / FCC	•
RoHS / WEEE	•	•	•	•